

DLBC15 - Dell M630 - 256GB

Dell M630

Intel Xeon E5-2667 v4 3.2GHz,2 5M Cache,9.60GT/s QPI,Turbo,HT ,8C/16T (135W) Max Mem 2400MHz

256GB - Dual In-Line Memory Module,32GB,2400,2RX4,8G,DDR4,R

Intel X710 Dual Port, 10Gb KR Blade Network Daughter Card

QLogic QME2662 16Gbps Fibre Channel I/O Card

H730 Controller

iDRAC8 Enterprise

BIOS/UEFI INFORMATION
Mechanical Overview
Front View
Rear View
Memory Information
Memory Population
Icon Legend
System Status
CPU
vFlash Media

Memory Information
Memory Population
Configuration: 1 2 3 4 5 6 7 8 9 10 11 12
Memory Optimized
Advanced ECC or Erroring
Memory sparing details are documented in the Owner's Manual

Icon Legend
System Status
CPU
vFlash Media

Memory Card
MEZZ1_FAB_C
MEZZ2_FAB_B

Internal USB Key
Internal USB Key

Caution
Memory (DIMM) and CPU(s) may be hot during operation.
Many repairs may only be done by a certified service technician. You should only perform troubleshooting and simple repairs as authorized in your product documentation, or as directed by the service or telephone support and support team. Damage due to servicing that is not authorized by Dell is not covered by your warranty. Read and follow the safety instructions that come with this product.
To learn more about this Dell product or order additional or replacement parts, go to Dell.com/support
© 2015 Dell Inc. All Rights Reserved. Rev A01 Label Part No. XP340

ASSET

COA



GKP2LH2



Service GKP2LH2
Express 36079952438
Code Mfg. Date: 20170614

DELL

服务器 / 伺服器

Reg Model: HHB

Reg Type: HHB005

V / 额定电压 / 额定電壓: 12 V

A / 额定电流 / 额定電流: 37A



FCC1

DP/N: 7V150 A00

DELL Reg Model / 产品型号 / 產品型號: HHB
Reg Type: HHB005
VCCI
MSIP-REM-E2K-HHB005
R33002 RoHS
IS 13252 (Part 1)/ IEC 60950-1
E105106
R-41000988
EN 60950-1
YUVH
Assembled in Mexico / 生产地: 墨西哥 / 生產地: 墨西哥
DP DP/N: HTPP2 A00 JSD2 FCC2





Revision #2

Created 21 December 2024 19:24:17 by Andy

Updated 21 December 2024 19:28:58 by Andy